

Comfort Fit Utility Belt

Installation and Usage Instructions BELTCMFT Series

Please read instructions carefully and fully before installation and/or usage.



IMPORTANT NOTES

- Do **not** attach individual tools heavier than 6lbs to belt
- Be sure to use suitable attachments around the webbing portion only
- Add and remove pockets and tool lanyards from belt only when in safe location
- Be aware of the hazard of snagging when climbing
- Do not connect directly to vertical webbing loops (figure 1)
- D-Rings, included with BELTCMFTD Models, are for storing tools (figure 2)



Figure 1



Figure 2

WARNINGS

ALWAYS WEAR APPROPRIATE PROTECTIVE EQUIPMENT. DO NOT USE THIS PRODUCT ON OR NEAR ROTATING EQUIPMENT. IMPROPER USE COULD RESULT IN DEATH OR DISMEMBERMENT. IF ANY CRACKS, RIPS OR TEARS ARE NOTED, PRODUCT REPLACEMENT IS REQUIRED.

PUTTING ON BELT

Step 1



Tighten padded part around waist and connect hook and loop.

Step 2



Clip webbing and tighten webbing by pulling on the end.

INSTALLING POCKETS

Step 1



While wearing the belt determine a suitable location and spacing by holding the tool pocket or pouch up to the belt.

Step 2



Remove the belt and unthread the webbing to the desired loop.

Step 3



Thread the pocket and the remaining loops.

Sizing:

Regular: 28" to 40" Waists

Large: 40" to 54" Waists

TY-FLÖT

Ty-Flot, Inc. • 305 Massabesic Street • Manchester, NH 03103
www.ty-flot.com • Phone: 603-669-5169 • Fax: 603-669-5113

CUTTING-EDGE PREVENTION™